

| Size                | LR/PR | Service Index      | Tread Depth (32nds) | Standard Rim | Overall Diameter (inch) | Section Width (inch) | Max. Load Capacity at Cold Inflation Pressure |      |     |     |      |      |     |     |
|---------------------|-------|--------------------|---------------------|--------------|-------------------------|----------------------|---|------|-----|-----|------|------|-----|-----|
|                     |       |                    |                     |              |                         |                      | Single  |      |     |     | Dual |      |     |     |
|                     |       |                    |                     |              |                         |                      | kg  | lbs  | kpa | psi | kg   | lbs  | kpa | psi |
| 11R22.5(CR926D)     | H/16  | 148/145M           | 21                  | 8.25         | 41.5                    | 11.0                 | 3150  | 6940 | 850 | 123 | 2900 | 6390 | 850 | 123 |
| 11R24.5(CR926D)     | H/16  | 149/146L           | 21                  | 8.25         | 43.5                    | 11.0                 | 3250  | 7160 | 830 | 120 | 3000 | 6610 | 830 | 120 |
| 255/70R22.5(CR926D) | H/16  | 140/137L           | 18                  | 7.50         | 36.6                    | 10.0                 | 2500  | 5510 | 830 | 120 | 2300 | 5070 | 830 | 120 |
| 295/80R22.5(CR926D) | H/16  | 150/147M           | 20                  | 9.00         | 41.1                    | 11.7                 | 3350  | 7390 | 830 | 120 | 3075 | 6780 | 830 | 120 |
| 295/80R22.5(CR926D) | J/18  | 152/149L           | 20                  | 9.00         | 41.1                    | 11.7                 | 3550  | 7830 | 900 | 131 | 3250 | 7160 | 900 | 131 |
| 315/80R22.5(CR926B) | J/18  | 154/151M(156/150L) | 21                  | 9.00         | 42.4                    | 12.3                 | 3750  | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |
| 315/80R22.5(CR926B) | L/20  | 157/154K           | 21                  | 9.00         | 42.4                    | 12.3                 | 4125  | 9090 | 900 | 130 | 3750 | 8270 | 900 | 130 |
| 7.50R16(CR926)      | G/14  | 122/118L           | 15                  | 6.00G        | 31.7                    | 8.5                  | 1500  | 3305 | 770 | 112 | 1320 | 2910 | 770 | 112 |
| 10.00R20(CR926)     | J/18  | 149/146J           | 20                  | 7.50         | 41.5                    | 10.9                 | 3250  | 7160 | 930 | 135 | 3000 | 6610 | 930 | 135 |
| 11.00R20(CR926)     | J/18  | 152/149K           | 20                  | 8.00         | 42.7                    | 11.5                 | 3550  | 7825 | 930 | 135 | 3250 | 7165 | 930 | 135 |
| 12.00R20(CR926)     | J/18  | 154/151K           | 22                  | 8.50         | 44.3                    | 12.4                 | 3750  | 8270 | 830 | 120 | 3450 | 7610 | 830 | 120 |
| 12.00R24(CR926B)    | L/20  | 160/157K           | 24                  | 8.50         | 48.3                    | 12.4                 | 4500  | 9920 | 900 | 131 | 4125 | 9090 | 900 | 131 |
| 12R22.5(CR926)      | J/18  | 152/149L           | 20                  | 9.00         | 42.7                    | 11.8                 | 3550  | 7830 | 930 | 135 | 3250 | 7160 | 930 | 135 |
| 13R22.5(CR926)      | J/18  | 156/151K           | 20                  | 9.75         | 44.3                    | 12.6                 | 4000  | 8820 | 875 | 128 | 3450 | 7610 | 875 | 128 |