

Size	LR/PR	Service index	Tread Depth (32nds)	Standard Rim	Overall Diameter (inch)	Section Width (inch)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							kg	lbs	kpa	psi	kg	lbs	kpa	psi
11R22.5	G/14	144/142L	18	8.25	41.5	11.0	2800	6175	720	105	2650	5840	720	105
11R22.5	H/16	148/145M	18	8.25	41.5	11.0	3150	6940	850	123	2900	6390	850	123
295/75R22.5	G/14	144/141L	18	9.00	39.9	11.7	2800	6175	760	110	2575	5675	760	110
11R24.5	G/14	146/143L	18	8.25	43.5	11.0	3000	6610	720	105	2725	6005	720	105
11R24.5	H/16	149/146L	18	8.25	43.5	11.0	3250	7160	830	120	3000	6610	830	120
285/75R24.5	G/14	144/141L	18	8.25	41.3	11.1	2800	6175	760	110	2575	5675	760	110
215/75R17.5	H/16	135/133J	16	6.00	30.2	8.3	2180	4805	850	123	2060	4540	850	123
235/75R17.5	H/16	143/141J	17	6.75	31.4	9.2	2725	6005	875	128	2575	5675	875	128
225/70R19.5	G/14	128/126N	16	6.75	31.9	8.9	1800	3970	760	110	1700	3750	760	110
245/70R19.5	H/16	136/134M	16	7.50	33.0	9.8	2240	4940	830	120	2120	4675	830	120
265/70R19.5	J/18	143/141J	18	7.50	34.1	10.3	2725	6005	850	123	2575	5675	850	123
285/70R19.5	H/16	146/144K	18	8.25	35.2	11.1	3000	6610	850	123	2800	6175	850	123
315/70R22.5	L/20	156/150L	19	9.00	39.9	12.3	4000	8820	900	130	3350	7390	900	130