

Size	LR/PR	Service Index	Tread Depth (32nds)	Standard Rim	Overall Diameter (inch)	Section Width (inch)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							kg	lbs	kpa	psi	kg	lbs	kpa	psi
255/70R22.5	H/16	140/137M	18	7.5	36.6	10.0	2500	5510	830	120	2300	5070	830	120
275/70R22.5	H/16	148/145M	18	8.25	37.7	10.9	3150	6940	900	130	2900	6395	900	130
275/80R22.5	H/16	149/146M	18	8.25	39.8	10.9	3250	7165	850	123	3000	6610	850	123
385/65R22.5	J/18	158L(160K)	20	11.75	42.2	15.3	4250	9370	850	125	-	-	-	-
385/65R22.5	L/20	160K(158L)	20	11.75	42.2	15.3	4500	9920	900	130	-	-	-	-
425/65R22.5	L/20	165K	19	12.25	44.3	16.9	5150	11340	830	120	-	-	-	-
445/65R22.5	L/20	169K	19	13.00	45.3	17.5	5800	12775	900	130	-	-	-	-
11R22.5	H/16	148/145M	20	8.25	41.5	11.0	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149L	20	9.00	42.7	11.8	3550	7830	930	135	3250	7160	930	135
295/80R22.5	J/18	152/149M	19	9.00	41.1	11.7	3550	7830	900	131	3250	7160	900	131
10.00R20	H/16	146/143K	19	7.5	41.5	10.9	3000	6610	830	120	2725	6005	830	120
10.00R20	J/18	149/146J	19	7.5	41.5	10.9	3250	7160	930	135	3000	6610	930	135
11.00R20	J/18	152/149K	20	8.0	42.7	11.5	3550	7825	930	135	3250	7165	930	135